

# Ecoline 115W

## OUTDOOR LUMINAIRE



## NL-ECL-580×305-115W-xx

### PRODUCT SPECIFICATIONS

Product code	NL-ECL-580×305-115W-xx
Voltage	220 V - 240 V
LED driver	OSRAM OT165/170-240/1A04DIMLT2E
System power	115 W
Frequency	50–60 Hz
Power factor (PF)	0,95
LED type	Alder AS-5258WxA2-C2C210-0303
Number of LEDs	60 pcs
Beam angle	150°/65°
PCB material	aluminum
Dimensions	580 mm × 305 mm × 185 mm
Weight	6,6 kg
Protection	IP65
Operating temperature (tc)	-30° C – +75° C
Ambient temperature (ta)	-30° C – +50° C
Lifetime (L70)	min. 70 000 h
Color rendering index	Ra>80
Housing color	grey



MADE IN EU

IP65

IK08

DALI

CLO

ASTRO  
DIM

MAINS  
DIM

STEP  
DIM



*LED driver is separated from LED module*



*Adjustable tilt angle*

# Ecoline 115W

## OUTDOOR LUMINAIRE



### COLOR TEMPERATURE AND LUMINOUS FLUX

order no.	product code	color temperature	CCT	luminous flux
51775-65	NL-ECL-580×305-115W-WC	cold white	6 500 K	15 840 lm
51775-50	NL-ECL-580×305-115W-WD	daylight white	5 000 K	15 840 lm
51775-40	NL-ECL-580×305-115W-WN	normal white	4 000 K	15 840 lm
51775-30	NL-ECL-580×305-115W-WW	warm white	3 000 K	14 260 lm

### PRODUCT FEATURES


The Ecoline 115W, manufactured with the latest Alder LED technology, is designed for outdoor lighting of roads, car parks and buildings.

The Ecoline Series is equipped with the AstroDIM feature, which allows additional energy savings in twilight phases. Furthermore, MainsDIM for dimming via reduction of line voltage amplitude and DALI for intelligent light management. A constant luminous flux can be set by using the CLO function.

The luminaire has an integrated surge protection and it is suitable for poles with a diameter of max 60mm.



Uniform light distribution by using asymmetric optics



### Similar products:

#### Ecoline 80W

order no.	product code	color temperature	CCT	luminous flux
51760-65	NL-ECL-540×260-80W-WC	cold white	6 500 K	11 020 lm
51760-50	NL-ECL-540×260-80W-WD	daylight white	5 000 K	11 020 lm
51760-40	NL-ECL-540×260-80W-WN	normal white	4 000 K	11 020 lm
51760-30	NL-ECL-540×260-80W-WW	warm white	3 000 K	9 930 lm